



## MA-WA3560-DS7P

## 350 MHz 6.0 GHZ Multi Band Dual Slant Directional Antenna

MARS Multi Band Antenna covers all the bands for LTE, 3G, 2.5G and 2G cellular, as well as ISM, Wi Fi, WLAN, Bluetooth, GSM 900 and GSM 1900.

The antenna is aesthetic and has an unobtrusive profile that blends easily with any environment.

Easy installation makes this antenna highly recommended as an outstanding logistic solution for outdoor installations as well as in-building installations.



| Specifications  |   |            |           |             |          |  |
|---|---|------------|-----------|-------------|----------|--|
| Electrical  |   |            |           |             |          |  |
| Frequency range   | 350-400                                       | 698–960    | 1.7–2.7   | 3.3-3.8 GHz | 5.15-6.0 |  |
|   | MHz   | MHz        | GHz       |             | MHz      |  |
| Gain, typ.  | 1.5 dBi                                       | 7.5 dBi    | 6 - 7 dBi | 7 dBi       | 6 dBi    |  |
| VSWR typ.<br>max.   | 1.5 : 1                                       | 1.5 : 1    | 1.3 : 1   | 1.7:1       | 1.5 : 1  |  |
|   | 2.5 : 1                                       | 2.8 : 1    | 2.2 : 1   | 2.5:1       | 2.5 : 1  |  |
| Polarization  | Dual Slant ± 45° or Dual Pol in Diamond Shape |            |           |             |          |  |
| Port to Port Isolation, min.                                | -10 dB  | -25 dB     | -40 dB    | -28 dB      | -30 dB   |  |
| 3dB Beam-Width, Azimuth, typ.                               | 170°  | 75°        | 100°      | 80 °        | 40°      |  |
| 3dB Beam-Width, Elevation, typ                              | 170°  | 75°        | 100°      | 80 °        | 40°      |  |
| 3dB Beam-Width, H-Plane, typ.                               | 180°  | 90°        | 105°      | 90 °        | 50°      |  |
| 3dB Beam-Width, E-Plane, typ                                | 30 °  | 60°        | 95°       | 30 °        | 30°      |  |
| Front to Back Ratio, min                                    | -15 dB  |            |           |             |          |  |
| PIM, typ.   | -150 dBc                                      |            |           |             |          |  |
| Input power, max.   | 50 Watt                                       |            |           |             |          |  |
| Impedance   | 50 Ohm  |            |           |             |          |  |
| Mechanical  |   |            |           |             |          |  |
| Dimensions (HxWxD)  | 300 x 300 x 99 mm (12.2" x 12.2" x 4.96" )    |            |           |             |          |  |
| Connector   | See Ordering Options                          |            |           |             |          |  |
| Weight  | 900 gr.                                       |            |           |             |          |  |
| Mounting  | See Ordering Options                          |            |           |             |          |  |
| Radome  | UV Protected Plastic                          |            |           |             |          |  |
| Back Plane Aluminum protected through chemical passivation. |   |            |           |             |          |  |
| Environmental   |   |            |           |             |          |  |
| Operating Temperature Range                                 | -55°C to +65°C                                |            |           |             |          |  |
| Vibration   | According to IEC 60721-3-4                    |            |           |             |          |  |
| Wind Load   | 200 Km/h (Survival)                           |            |           |             |          |  |
| Flammability  | UL94  |            |           |             |          |  |
| Water Proofing  | -   | IP-67      |           |             |          |  |
| Humidity  | ETS 300 019-1-4,EN 302 085 (Annex A.1.1)      |            |           |             |          |  |
| Salt Fog  | According to                                  | IEC 68-2-1 | 1         |             |          |  |

**Specifications** 

## **Ordering Options**

| MA-WA3560-DS7P  | Antenna with 2 x 4.3-10 Female connectors, suited for MNT-22 Mount |
|-----------------|--|
| MA-WA3560-DS7PB | Antenna with 2 x 4.3-10 Female with MNT-22 Mount                   |
| MA-WA3560-DS7   | Antenna with 2 x N-type Female connectors, suited for MNT-22 Mount |
| MA-WA3560-DS7B  | Antenna with 2 x N-type Female connectors with MNT-22 Mount        |

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor St. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com