# Product Specifications





## F4A-HPNMNM-1M

FSJ4-50B SureFlex® Jumper with interface types N Male and N Male, 1 m

# **General Specifications**

Body Style, Connector A Straight
Body Style, Connector B Straight
Cable Family FSJ4-50B
Interface, Connector A N Male
Interface, Connector B N Male
Nominal Size 1/2 in

Length 1.000 m | 3.281 ft

Specification Sheet Revision Level A

# **Electrical Specifications**

3rd Order IMD Static Test Method Two +43 dBm carriers

3rd Order IMD, typical -112.00 dBm | -155.00 dBc (relative to carrier)

DTF, Connector A -34.00 dB DTF, Connector B -34.00 dB

# **Jumper Assembly Sample Label**



### **Return Loss/VSWR**

Frequency Band	VSWR, typical	Return Loss, typical (dB)
680-960 MHz	1.07	30.00
1700-2200 MHz	1.07	30.00
2200-2700 MHz	1.11	26.00

# **Regulatory Compliance/Certifications**

# Product Specifications



F4A-HPNMNM-1M

### **Agency**

RoHS 2011/65/EU China RoHS SJ/T 11364-2006 ISO 9001:2008

### Classification

Compliant by Exemption
Above Maximum Concentration Value (MCV)
Designed, manufactured and/or distributed under this quality management system





## **Included Products**

FSJ4-50B — FSJ4-50B, HELIAX® Superflexible Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket