



MA-WA3560-DS7P

350 MHz 6.0 GHZ Multi Band Dual Slant Directional Antenna

MARS Multi Band Antenna covers all the bands for LTE, 3G, 2.5G and 2G cellular, as well as ISM, Wi Fi, WLAN, Bluetooth, GSM 900 and GSM 1900.

The antenna is aesthetic and has an unobtrusive profile that blends easily with any environment.

Easy installation makes this antenna highly recommended as an outstanding logistic solution for outdoor installations as well as in-building installations.



Specifications							
Electrical							
Frequency range		350-400	698–960	1.7–2.7	3.3-3.8 GHz	5.15-6.0	
		MHz	MHz	GHz		MHz	
Gain, typ.		1.5 dBi	7.5 dBi	6 - 7 dBi	7 dBi	6 dBi	
VSWR	typ.	1.5 : 1	1.5 : 1	1.3 : 1	1.7:1	1.5 : 1	
	max.	2.5 : 1	2.8 : 1	2.2 : 1	2.5:1	2.5 : 1	
Polarization		Dual Slant ± 45° or Dual Pol in Diamond Shape					
Port to Port Isolation, min.		-10 dB	-25 dB	-40 dB	-28 dB	-30 dB	
3dB Beam-Width, Azimuth, typ.		170°	75°	100°	80 °	40°	
3dB Beam-Width, Elevation, typ		170°	75°	100°	80 °	40°	
3dB Beam-Width, H-Plane, typ.		180°	90°	105°	90 °	50°	
3dB Beam-Width, E-Plane, typ		30 °	60°	95°	30 °	30°	
Front to Back Ratio, min		-15 dB					
PIM, typ.		-150 dBc					
Input power, max.		50 Watt					
Impedance		50 Ohm					
Mechanical							
Dimensions (HxWxD)		300 x 300 x 99 mm (12.2" x 12.2" x 4.96")					
Connector		See Ordering Options					
Weight		900 gr.					
Mounting		See Ordering Options					
Radome		UV Protected Plastic					
Back Plane	Back Plane		Aluminum protected through chemical passivation.				
			onmental				
Operating Tempe	rature Range	-55°C to +65°C					
Vibration		According to IEC 60721-3-4					
Wind Load		200 Km/h (Survival)					
Flammability		UL94					
Water Proofing		IP-67					
Humidity		ETS 300 019-1-4,EN 302 085 (Annex A.1.1)					
Salt Fog		According to IEC 68-2-11					

Specifications

Ordering Options

MA-WA3560-DS7P	Antenna with 2 x 4.3-10 Female connectors, suited for MNT-22 Mount
MA-WA3560-DS7PB	Antenna with 2 x 4.3-10 Female with MNT-22 Mount
MA-WA3560-DS7	Antenna with 2 x N-type Female connectors, suited for MNT-22 Mount
MA-WA3560-DS7B	Antenna with 2 x N-type Female connectors with MNT-22 Mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor St. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com